

LEDGEROCK®

THE COMMERCIAL RETAINING WALL SYSTEM

PRODUCT & INSTALLATION GUIDE



PRODUCED BY NORTH STAR STONE AND MASONRY

LEDGEROCK[®]

THE COMMERCIAL RETAINING WALL SYSTEM



CURB APPEAL

The multiple faces of LedgeRock were molded uniquely for North Star Stone and Masonry from actual Falkstone, a native Mid-western stone face.

STRONG

The large-format, interconnecting design allows for walls up to 10' high without grid.

COST EFFECTIVE

Installation is less labor-intensive than conventional SRW's which makes LedgeRock projects quick and easy.

VERSATILE

LedgeRock can be stained with solid or blended color after installation which allows the installer to create a fluid, aesthetic color to compliment any application.

Approximate block weights & dimensions:

Unit	Pieces/ Cube	Block Height	Block Width*	Block Depth*	Block Weight	Sq. Ft./ Face	Cube Weight
Full Block	1	24"	48"	28"	2,474 lb.	8	2,474
Corner Block	1	24"	52"	28"	2,717 lb.	12	2,717
Half Block	2	24"	24"	28"	1,173 lb.	4	2,346
Corner Half Block	2	24"	28"	28"	1,406 lb.	8	2,812
Key Block	1	24"	44"	28"	2,258 lb.	7½	2,258
Full Recess	1	24"	48"	28"	2,025 lb.	8	2,025
Corner Recess	1	24"	52"	28"	2,306 lb.	12	2,306
Half Recess	2	24"	24"	28"	966 lb.	4	1,932
Corner Half Recess	2	24"	28"	28"	1,289 lb.	8	2,578
Base Block	1	24"	48"	52"	4,400 lb.	8	4,400
Half Base	2	24"	24"	52"	1,890 lb.	4	3,780

*Block depth and corner width include 4" for variant depth textured face



FULL BLOCK

- 8 sq. ft. per block for optimal coverage (12 sq. ft. per corner block)
- Steps back 2" per course
- Tapered sides allows for gradual curves
- Available in standard, recessed, corner, and corner recessed (corners offered in both right- and left-hand)
- Full block have two connectors on top which fit into the bottom channel of the next row
- Recessed allows to bring topping (sod, mulch, etc) to the lip of the wall

HALF BLOCK

- Half the size of full block optimal fitting
- Steps back 2" per course
- Tapered sides allows for gradual curves
- Available in standard, recessed, corner, and corner recessed (corners offered in both right- and left-hand)
- Helps to maintain the wall's running bond pattern
- Half block have one connector on top which fit into the bottom channel of the next row
- Conveniently packaged two blocks per pallet



KEY BLOCK

- 4" shorter than full block for optimal fitting
- Steps back 2" per course
- Tapered sides allows for gradual curves
- Available in standard and recessed
- Key block maintains wall's running bond when using corner blocks (for each corner block the row loses 2" in setback)*

* Example, if using corner block on both sides of a wall, you lose 4" per course and will need to use 1 key block on the 2nd course, 2 on the 3rd course, 3 on the 4th course, and so on until you get to the 12th course where a key block is not necessary. Begin pattern again at the 13th course.

BASE BLOCK

- 24" deeper than full block for additional strength
- Steps back 2" per course
- Allows you to build up to 10' high without grid
- Tapered sides allows for gradual curves





northstarmasonry.com

North Star Stone and Masonry

2173 NW 76th Street, Medford MN 55049

800.562.6633 | 507.451.7278

We reserve the right to improve our products and make changes in the specifications and design without notice. The information contained herein was compiled in good faith to accurately represent the products and applications which are illustrated. Final determination of the suitability for the use contemplated and its manner of use are the sole responsibility of the user.